

Prestressed Lintels

| |
|--------|
| CI/SfB |
| 31.9 |

NAYLOR
L I N T E L S

EMAIL: LINTELS@NAYLOR.CO.UK
WEB: WWW.NAYLORLINTELS.CO.UK

FREEPHONE TECHNICAL HOTLINE:
0800 5424192



UK's leading
manufacturer of
concrete lintels



Index of Products

| | |
|-----------------------------------|-----------|
| Introduction | 1 |
| Lintels Range | 2 |
| Design Service | 5 |
| Installation | 6 |
| Hi-Spec Range | 7 |
| Specials Service | 10 |
| Ultra-Fire Range | 11 |
| Fire-Spec Range | 12 |
| Steel Range | 16 |
| Economy Range | 17 |
| Padstone Range | 18 |
| COSHH Information | 19 |

Useful Contacts

Free Technical Hotline 0800 5424192

Sales Telephone 01924 267286

Sales Fax 01924 265674

www.naylorlintels.co.uk

For brochure downloads & case studies

Specifications@naylor.co.uk

For drawing emails and schedule requests

Technical@naylor.co.uk

For specific bespoke requirements and to request a visit from our technical staff

Enquiries@naylor.co.uk

For sales, prices and delivery requirements

Lintels@naylor.co.uk

For orders or to request information

Introduction

Naylor, a manufacturer of building materials since 1890 combines a wealth of experience in manufacturing techniques and in-depth ranges with a reputation for quality products, service and value for money.

The Naylor lintel range has been continually improved and enhanced over the last 30 years in response to ever changing customer requirements and needs. The result is an unrivalled range offering lintels to suit every situation, backed up by a speedy and efficient specials service.

Nationwide Stockists

Naylor produce annually over 1 million metres of lintels. As well as having stocks of over 100 standard sections of lintels, Naylor are also able to supply specials at short notice. Naylor Lintel Stockists are therefore offered an unrivalled range of prestressed concrete lintels for both industrial and commercial use.

Naylor Lintel Stockists are located throughout the UK to give back-up and local supply facilities to the end user.

Technical Services

A free design and technical service is available and advice is given for particular requirements and applications. Lintel schedules and calculations can be provided from working drawings.

Naylor Lintels can be specified from the NBSPlus Clause F30:740.

Drawings may be e-mailed directly to: specifications@naylor.co.uk

Features and Benefits

- The widest range of any Prestressed Lintels available from one manufacturer in the UK
- A nationwide delivery service and nationwide prices, regardless of site destination
- Guaranteed quality and consistency
- Free technical support and help to anywhere in the UK
- Unrivalled specials service
- Multi product deliveries, you can add clay & plastic pipes & fittings to any delivery
- A simple pricing policy, you only pay per metre so there are no extra charges for a specific length
- All lintels are clearly marked and removing any risk on site that the wrong lintel might be built in
- Close quality control and fire tolerances are achieved in our modern and innovative factory
- An unrivalled specials service where we can manufacture any design, length or strength of lintel that you require
- A free Scheduling service
- A free Technical Hotline and Backup service
- We will come and see you to discuss your lintel, delivery and site requirements and answer your technical questions

Naylor Lintels Range



Hi-Spec Range

The best performing Concrete Lintels on the UK Market. All units are pre-stressed to ensure optimum performance and come with 30 minutes fire rating as standard. With a range of 19 different sections sizes and with lengths available up to 6200mm on certain sections sizes. Due to additives these units are suitable for use below ground. Different reinforcement type and position than that used in our economy range.

Finish

An ex-steel mould finish and made from wet cast concrete. Possibility of small air holes on the surface, aggregate and concrete fines to bottom arrises. For use normally in plastered situations. Not exposed situations.

Order/Specification Code

Use the Hi-Spec reference on our load tables (e.g. S5)



Fair Faced Range

A range of lintels with the same performance and fire rating as the standard Hi-Spec range but with a smooth, consistent colour finish.

Finish

Type C Fair Faced finish.

All corners and arrises and faces on the lintel are perfect.

Order/Specification Code

Prefix the Hi-Spec reference with the word Faced (e.g. Faced S5)



Colour-Spec Range

A range of lintels to suit a specific site requirement. The units can be coloured to over 500 different colours to match stone or blockwork. The colour penetrates the surface and gives consistency of colour.

Finish

Coloured finish perfectly smooth with perfect corners arrises and face and all units are hand finished.

Order/Specification Code

Prefix Hi-Spec reference with the word Colour (e.g. Colour S5)



Chem-Spec Range

A range of special lintels which can withstand aggressive and contaminated ground conditions, these units can also be used in effluent situations due to the additives that are used in this mix of concrete.

Finish

As per the Hi-Spec Range

Order/Specification Code

Prefix Hi-Spec reference with the words Chem (e.g. Chem S5)

Faced Fire Range

A range of lintels with the same fire resistance properties as our Fire-Spec range but with the same finish as our Fair Faced units that are designed to be used in fair faced, paintgrade and blockwork situations, These units can also be coloured upon request.

Finish

Type C Fair Faced finish.

All corners and arrises and face on the lintel are perfect and the units are hand finished.

Order/Specification Code

Prefix Hi-Spec reference with the words Faced Fire (e.g. FacedFire S5)



Fire-Spec Range

A range of lintels with enhanced fire resistance, 140mm wide units can achieve 90 minutes, 190mm and 215mm wide units can achieve 120 minutes fire resistance. All units comply with BS8110 Table 4.3 section 2 and as a result have a slightly less load bearing capacity when compared with the Hi-Spec Range

Finish

An ex-steel mould finish and made from wet cast concrete. May see small air holes on the surface and concrete fines to bottom arrises. For use normally in plastered situations. Not exposed situations.

Order/Specification Code

Prefix Hi-Spec reference with the word Fire (e.g. Fire S5)



Ultra-Fire Range

Our newest range of lintels with an enhanced fire resistance. Due to the special coating applied in this dual cast product, 100mm wide units can achieve 90 minutes fire resistance as standard, and 140mm wide and 215mm wide units can achieve 240 minutes. The lintels also comply with BS8110 table 4.3 section 2.

Finish

These lintels have a slightly different texture to concrete but are smooth and are ideally suited to paint grade or exposed situations. They can also be left natural but we would advise the use of a waterproof sealant to reduce surface dusting.

Order/Specification code

As per the product range (e.g. Ultra-Fire 100-6, Ultra-Fire 100-9, Ultra-Fire 140-9, Ultra-Fire 215-9.)



Specials Service

At Naylor's we do not only manufacture lintels - anything in concrete can be made to a high standard, because we are innovators in prestressed and pre-cast concrete, we pride ourselves in offering solutions to the industry, whether it be curved on plan, curved on elevation, special sizes, particular strength or section requirements, special applications or just want to reduce the risks with on site casting, we can offer a cost effective solution. All units are cast to B.S. tolerances, with a wide range of finishes and casting details available. We can manufacture lengths up to 8 mtrs long and 1 mtr wide with the maximum weight available per unit of 4 tonnes. We work with you to find a solution at a competitive price and our technical team can visit you either on site or at your offices and manage the order from start to finish.





Padstones

A full range of padstones are available with a strength that is a minimum of 50N/mm² and are suitable to take special fixing or any other site situations. We have a large range of 29 sections available as standard stock items with an additional 6 L-shaped padstones available. Specials can be made also at a competitive price and the quality assures you that the concrete will take any loads placed upon it. Special strength higher than 50N are also available on request



Economy Range

A cost effective fully reversible unit for when you have a standard housing situation or small load situation.

Finish

An ex-steel mould finish and made from wet cast concrete. May see small air holes on the surface, aggregate and concrete fines to bottom arrises. For use normally in plastered situations. For exposed situations see Fair Faced Range

Order/Specification Code

Please see the Economy Load Tables (e.g. ER1, ER2 etc)



L-Strip Steel Range

A range of Steel L-Shaped angle lintels suitable for brick and stone to carry the external leaf.

Available in galvanised (Pregalv G600) and stainless steel grade 304. Other specially designed steel lintels available upon request.

Design Service



A free design and technical service is available and advice and guidance gladly given for any particular requirements and applications. Lintel calculations and schedules can be provided from working drawings and solutions offered for any specific design, colour, finish, shape, curve or fire requirement.

Drawings can be emailed directly to:
specifications@naylor.co.uk
or to discuss call: 0800 5424192.

Specification

British Standards and Design

The design of Naylor Prestressed Lintels complies with BS8110:part 1: 1997: Section 4.

Naylor Lintels are Manufactured in accordance with BSEN845 part 2: 2003.

Materials used in the manufacture of Naylor Prestressed Lintels comply with BSEN206 and BS8500. The prestressing wire complies with BS5896.

Naylor Lintels have a low water absorption and as a result of the quality controlled hi spec dense concrete mix used in their manufacture, they can be used underground providing that the ends of the units are encased in a minimum of 45mm of mortar to the ends of the reinforcing strands.

All Naylor Lintels are wet cast and have a concrete strength of 50 kN/mm² and are suitable to accept fixings providing that the tendons contained inside the unit remain undamaged.

All fire rated Lintels produced by Naylor Lintels comply with BS8110:table 4.3:section 2:1985.

All L-Strip are manufactured from steel complying with BSEN10025 with a minimum yield stress of 275N/mm². Zinc coating is galvanised to BS2989z2. Stainless Steel L-Strip is also produced, conforming to grade 304:S15:BS1449:Part 2.

Compliance with Building Regulations Part L and Part E

Implementation of the amendments to part E and L of the Building Regulations came into force in 2002. Amongst the new measures it is required that the thermal bridging and fabric insulation be improved (part L) and the resistance to sound reverberation, especially at low frequencies, required (Part E) be increased.

Compliance with the new regulations can easily be achieved using our Hi-Spec range of lintels.

Scope of manufacture

Lintels can be manufactured to lengths up to 6000mm dependant upon the section size.

Lintels can also be cast with inserts, channels and fixings.

Specials can be made any shape or size to a maximum weight of 4 tonnes, 8000mm length and 2000mm width radius lintels available from a minimum radius of 585mm and any maximum radius available.

Lintel end bearing

Lintels are usually supplied with the following allowances for bearing at each end unless otherwise stated.

- 100mm for openings up to and including 1000mm
- 150mm for openings up to and including 3000mm
- 200mm for openings over 3000mm

It is however the responsibility of the building designer to ensure that these end bearings are sufficient to ensure that there is no over stressing of the masonry at the supports.

Installation - code of practice

Concrete Lintels

All Hi-Spec and Fair Faced lintels are marked 'TOP'. This surface should remain uppermost at all times unless the units are being used in a cantilever situation. It is important that the lintels are installed the correct way according to the load bearing situation. If the mark 'TOP' cannot be seen then the unit should be placed so that the reinforcement strand is close to the bottom of the unit and away from the load that is imposed.

Naylor Economy range is fully reversible and can be installed in either direction. As a consequence these units are not marked.

All lintels should be bedded on a level full mortar bed.

All wall ties, damp proof courses and weep vents should comply with the current building regulations.

Where possible it is advised that on cavity wall construction that both internal and external leaves should be built uniformly.

For spans greater than 1200mm it is good practice to provide temporary support at 1200mm centres. If the lintels are to be supporting a concrete floor a minimum lintel depth of 140mm is recommended to allow for impact loads during the actual placing of the concrete floor units.

Steel Lintels

All lintels should be bedded on a level full mortar bed. For spans greater than 1200mm temporary support should be used until the first 3 courses of masonry have matured sufficiently for the support to be removed. In certain cases the door frame, window frame or timber former for the opening are sufficient for this purpose but this is dependant upon the quality and material of the frame or former.

All wall ties, damp proof courses and weep vents should comply with the current building regulations.

Special Requirements

Should you have any special Lintel requirements that are not detailed in our standard range or wish to discuss any of our products in more detail please call our technical team on 0800 5424192 who will be more than happy to discuss your lintel requirements in more detail or arrange a visit to offer an appropriate solution.

Cutting

Concrete Lintels may be cut using a high speed diamond cutting disc. Use of such equipment should be by a properly trained operative who is aware of the health and safety requirements of the machine and the COSHH information for the product.

Under no circumstances should the Ultra-Fire Range of Lintels be cut down in size.

For Naylor Industries COSHH information which details Naylor Lintels Products, together with Handling and Storage please visit www.naylorlintels.co.uk or call our free technical hotline on 0800 5424192.

Hi-Spec Range



The best performing Concrete Lintels on the UK Market. All units are prestressed to ensure optimum performance and come with 30 minutes fire rating as standard. With a range of 19 different sections sizes and with lengths available up to 6200mm on certain sections sizes.






Finish





An ex-steel mould finish and made from wet cast concrete. May see small air holes on the surface, aggregate and concrete fines to bottom arrises. For use normally in plastered situations. Not exposed situations.





Order/Specification Code

Use the Hi-Spec reference on our load Tables (e.g. S5)

| Hi-Spec Range | | P100 | S4 | R6 | R9 | R12 |
|---|------------|--------|-------------------------|-------------------------|-------------------------|--|
| Load Table Units suitable for 100mm wide walls | | | | | | |
| Unfactored Loads in kN/m | | | | | | |
| Fire Resistance Available (mins) | | 30 | 30 | 30 | 30 | 30 |
| Suitable for Foundation Use | | yes | yes | yes | yes | yes |
| Maximum Stock Length Available | | 2400mm | 3000mm | 3600mm | 3600mm | 3600mm Longer lengths available on request. |
| Available Range Finish | | Chem | Faced Colour Chem | Faced Colour Chem | Faced Colour Chem | Faced Colour Chem |
| Length | Clear Span | 100x70 | 100x100 | 100x140 | 100x215 | 100x290 |
| 900mm | 700mm | 17.67 | 34.27 | 50.74 | 78.18 | 100.05 |
| 1100mm | 900mm | 10.89 | 23.18 | 40.47 | 62.44 | 79.90 |
| 1200mm | 1000mm | 8.86 | 19.04 | 36.74 | 56.72 | 72.57 |
| 1500mm | 1200mm | 6.18 | 13.48 | 26.19 | 48.57 | 60.85 |
| 1800mm | 1500mm | 3.95 | 8.75 | 17.14 | 36.27 | 49.66 |
| 2100mm | 1800mm | 2.72 | 6.10 | 12.04 | 25.78 | 41.91 |
| 2400mm | 2100mm | 1.96 | 4.47 | 8.89 | 19.21 | 31.70 |
| 2700mm | 2400mm | n/a | 3.39 | 6.80 | 14.83 | 24.53 |
| 3000mm | 2700mm | n/a | 2.64 | 5.34 | 11.76 | 19.49 |
| 3300mm | 3000mm | n/a | n/a | 4.29 | 9.53 | 15.83 |
| 3600mm | 3300mm | n/a | n/a | 3.75 | 8.36 | 13.49 |
| Lintel Weight kg/m | | 17 | 26 | 35 | 53 | 69.6 |

| Hi-Spec Range | | P140 | R3 | S5 | R8 | R11 |
|---|------------|---|---|--|---|---|
| Load Table Units suitable for 140mm wide walls | |  |  |  |  |  |
| Unfactored Loads in kN/m | | | | | | |
| Fire Resistance Available (mins) | | 30 | 30 | 30 | 30 | 30 |
| Suitable for Foundation Use | | yes | yes | yes | yes | yes |
| Maximum Stock Length Available | | 2400mm | 3000mm | 3600mm | 3600mm | 3600mm |
| | | | | | Longer lengths available on request. | |
| Available Range Finish | | Chem | Faced Colour Chem | Faced Colour Chem | Faced Colour Chem | Faced Colour Chem |
| Length | Clear Span | 140x70 | 140x100 | 140x140 | 140x215 | 140x290 |
| 900mm | 700mm | 18.14 | 49.17 | 63.32 | 100.57 | 128.00 |
| 1100mm | 900mm | 11.15 | 33.04 | 50.50 | 80.31 | 102.20 |
| 1200mm | 1000mm | 9.06 | 27.08 | 41.89 | 72.95 | 98.82 |
| 1500mm | 1200mm | 6.31 | 19.11 | 29.81 | 62.22 | 77.58 |
| 1800mm | 1500mm | 4.00 | 12.38 | 19.49 | 41.60 | 63.30 |
| 2100mm | 1800mm | 2.73 | 8.62 | 13.67 | 29.53 | 51.38 |
| 2400mm | 2100mm | 1.96 | 6.31 | 10.07 | 21.97 | 38.35 |
| 2700mm | 2400mm | n/a | 4.79 | 7.68 | 16.93 | 29.64 |
| 3000mm | 2700mm | n/a | 3.74 | 6.03 | 13.40 | 23.53 |
| 3300mm | 3000mm | n/a | n/a | 4.83 | 10.83 | 19.09 |
| 3600mm | 3300mm | n/a | n/a | 4.20 | 9.49 | 16.25 |
| Lintel Weight kg/m | | 24 | 34 | 47 | 72 | 97.4 |

| Hi-Spec Range | | P190 | R2 | R190 | R13 |
|---|------------|---|---|---|---|
| Load Table Units suitable for 190mm wide walls | |  |  |  |  |
| Unfactored Loads in kN/m | | | | | |
| Fire Resistance Available (mins) | | 30 | 30 | 30 | 30 |
| Suitable for Foundation Use | | yes | yes | yes | yes |
| Maximum Stock Length Available | | 2400mm | 3000mm | 3600mm Longer lengths available on request. | 3600mm |
| Available Range Finish | | Chem | Faced Colour Chem | Faced Colour Chem | Faced Colour Chem |
| Length | Clear Span | 190x70 | 190x145 | 190x215 | 190x290 |
| 900mm | 700mm | 30.88 | 81.86 | 126.49 | 162.20 |
| 1100mm | 900mm | 19.02 | 60.78 | 101.00 | 126.49 |
| 1200mm | 1000mm | 15.48 | 50.12 | 91.72 | 117.60 |
| 1500mm | 1200mm | 10.79 | 35.69 | 70.66 | 97.99 |
| 1800mm | 1500mm | 6.88 | 23.34 | 46.87 | 79.77 |
| 2100mm | 1800mm | 4.72 | 16.36 | 33.22 | 56.74 |
| 2400mm | 2100mm | 3.41 | 12.03 | 24.68 | 42.28 |
| 2700mm | 2400mm | n/a | 9.17 | 18.98 | 32.63 |
| 3000mm | 2700mm | n/a | 7.17 | 14.99 | 25.85 |
| 3300mm | 3000mm | n/a | 5.73 | 12.08 | 20.92 |
| 3600mm | 3300mm | n/a | 4.98 | 10.56 | 17.77 |
| Lintel Weight kg/m | | 32 | 66 | 98 | 132.2 |

| Hi-Spec Range | | P215 | R7 | S8 | R14 |
|---|------------|---|---|---|---|
| Load Table Units suitable for 215mm wide walls | |  |  |  |  |
| Unfactored Loads in kN/m | | | | | |
| Fire Resistance Available (mins) | | 30 | 30 | 30 | 30 |
| Suitable for Foundation Use | | yes | yes | yes | yes |
| Maximum Stock Length Available | | 2400mm | 3600mm | 3600mm Longer lengths available on request. | 3600mm |
| Available Range Finish | | Chem | Faced Colour Chem | Faced Colour Chem | Faced Colour Chem |
| Length | Clear Span | 215x70 | 215x145 | 215x215 | 215x290 |
| 900mm | 700mm | 32.53 | 90.15 | 138.94 | 178.60 |
| 1100mm | 900mm | 20.02 | 63.86 | 110.93 | 142.58 |
| 1200mm | 1000mm | 16.29 | 52.65 | 92.25 | 129.48 |
| 1500mm | 1200mm | 11.35 | 37.48 | 74.26 | 107.73 |
| 1800mm | 1500mm | 7.23 | 24.49 | 49.23 | 83.95 |
| 2100mm | 1800mm | 4.96 | 17.15 | 34.87 | 59.68 |
| 2400mm | 2100mm | 3.57 | 12.60 | 25.89 | 44.45 |
| 2700mm | 2400mm | n/a | 9.59 | 19.89 | 34.28 |
| 3000mm | 2700mm | n/a | 7.49 | 15.69 | 27.14 |
| 3300mm | 3000mm | n/a | 5.97 | 12.63 | 21.94 |
| 3600mm | 3300mm | n/a | 5.18 | 11.04 | 18.62 |
| Lintel Weight kg/m | | 36 | 75 | 111 | 150 |

Specials Service



Here at Naylor's we pride ourselves on being innovative in our approach to all building problems and offering solutions. With our modern factory and stringent manufacturing processes we can work with you through the design process and on site installation to ensure your satisfaction is guaranteed.

“A Special lintel Manufacturer
with a Special Service”
(Fairhurst Architects)

At Naylor's we are constantly increasing our manufacturing capacity in order to improve our specials service even further. We can now manufacture any length and any section size in seven working days. We can design the reinforcement to meet a particular strength requirement should our Hi-Spec Range fail to meet the section size or strength requirement, we can provide you with any calculations as soon as an order is placed at no extra cost.

Our Company Representatives are available to come and see you in order to discuss any aspect of our business with you and are able to offer a solution to any on site problem that you may have. All our representatives have not only sales experience but site and practical building experience to offer you a cost effective solution. We also have a Free Technical Helpline that is available to offer a quick and free response to any questions connected with our method or scope of manufacture, and our design



teams are able to complete lintel designs to special fire requirements, prepare schedules and loading calculations for all orders or enquiries.

Although the majority of our work is in prestressed we are also available to manufacture pre-cast units to any shape size or dimension, these include any curved on plan lintels, bridge beams, structural beams, ground beams or anything that requires an increased fire rating above that of our normal fire range or our cutting edge ultra fire range that can achieve a 240 minute fire rating, section dependant.

Prestressed or
Pre-cast
it's your choice





Ultra-Fire Lintels



After months of hard work Naylor Lintels have developed a new and innovative range of lintels that can offer 90 minutes fire rating on a 100mm wide prestressed concrete Lintel and 240 minutes fire protection on 140mm and 215mm wide prestressed concrete Lintels. This will place Naylor Lintels in a unique position as the first Lintel Manufacturer to have developed a lintel that can comply with BS8110 and will solve many problems for architects and engineers alike. The lintels have already been used on developments in Manchester and have been specified on Paradise Street in Liverpool.

They are also attracting interest from EDF Energy and many other architects and engineers who are excited about now having a solution to building design and safety.



| Ultra-Fire Spec Range | | Ultra 100-6 | Ultra 100-9 | Ultra 140-9 | Ultra 215-9 |
|---|------------|---|---|---|---|
| Load Table | | 100mm wide walls | 100mm wide walls | 140mm wide walls | 215mm wide walls |
| The ultimate lintels for the ultimate fire protection | |  |  |  |  |
| Unfactored Loads in kN/m | | | | | |
| Fire Resistance Available (mins) | | 90 | 90 | 240 | 240 |
| Maximum Stock Length Available | | 2700mm | 3600mm | 3600mm | 3600mm |
| | | | | Longer lengths available on request | |
| Length | Clear Span | 100x145 | 100x215 | 140x215 | 215x215 |
| 900mm | 700mm | 35.17 | 79.32 | 109.50 | 139.20 |
| 1100mm | 900mm | 22.21 | 50.57 | 69.82 | 88.69 |
| 1200mm | 1000mm | 18.24 | 41.71 | 57.57 | 73.10 |
| 1500mm | 1200mm | 12.90 | 29.03 | 40.25 | 51.21 |
| 1800mm | 1500mm | 8.36 | 19.32 | 36.42 | 33.53 |
| 2100mm | 1800mm | 5.81 | 13.42 | 18.57 | 23.50 |
| 2400mm | 2100mm | 4.23 | 9.90 | 13.69 | 17.27 |
| 2700mm | 2400mm | 3.19 | 7.57 | 10.45 | 13.14 |
| 3000mm | 2700mm | n/a | 5.94 | 8.19 | 10.26 |
| 3300mm | 3000mm | n/a | 4.76 | 6.56 | 8.17 |
| 3600mm | 3300mm | n/a | 4.17 | 5.71 | 7.08 |
| Lintel Weight kg/m | | 35 | 53 | 72 | 111 |

All the above products have been awarded patent pending status (PAT-APP 0722871.1)

Fire-Spec Range



Fire-Spec Range

Naylor Fire-Spec range is our ex-steel mould finish high performance units, they are available in 60, 90 and 120 minutes, dependant upon the section width. Other concrete sections can be made with a fire resistance equal to or greater than our standard range and our technical team with their special knowledge of concrete can advise you on which sections would achieve a specific fire resistance and strength rating and offer a design solution should this not be detailed in our load span tables.

Fire-Spec References

To specify units from this range prefix the Hi-Spec reference with the word 'Fire'.

Example: Fire S5





Fair Faced Fire-Spec Range




Naylor Fair Faced Fire-Spec lintels are also available in a class C fair faced finish and again with a 60, 90 and 120 minute fire rating.




Fair Faced Fire-Spec References

To specify Units from this range prefix the Hi-Spec references with the word 'Faced Fire'

Example: Faced Fire S5

| Fire-Spec Range | | Fire R3 | | Fire S5 | | Fire R8 | | Fire R11 | |
|---|------------|---|---------|---|---------|---|---------|---|---------|
| Load Table Units suitable for 140mm wide walls | |  | |  | |  | |  | |
| Unfactored Loads in kN/m | | | | | | | | | |
| Maximum Stock Length Available | | 3000mm | | 3600mm | | 3600mm | | 3600mm | |
| | | | | | | Longer lengths available on request. | | | |
| Available Range Finish | | Faced Colour | | Faced Colour | | Faced Colour | | Faced Colour | |
| Fire Resistance in minutes | | 60 | 90 | 60 | 90 | 60 | 90 | 60 | 90 |
| Length | Clear Span | 140x100 | 140x100 | 140x140 | 140x140 | 140x215 | 140x215 | 140x290 | 140x290 |
| 900mm | 700mm | 40.72 | 20.92 | 63.32 | 44.81 | 100.57 | 101.52 | 128.00 | 129.32 |
| 1100mm | 900mm | 25.32 | 12.83 | 50.50 | 28.21 | 80.31 | 81.07 | 102.20 | 103.26 |
| 1200mm | 1000mm | 20.69 | 10.42 | 41.89 | 23.15 | 72.95 | 73.64 | 98.82 | 93.78 |
| 1500mm | 1200mm | 14.52 | 7.23 | 29.81 | 16.34 | 62.22 | 54.98 | 77.58 | 78.41 |
| 1800mm | 1500mm | 9.34 | 4.57 | 19.49 | 10.56 | 41.60 | 36.33 | 63.30 | 63.98 |
| 2100mm | 1800mm | 6.46 | 3.10 | 13.67 | 7.32 | 29.53 | 25.69 | 51.38 | 47.29 |
| 2400mm | 2100mm | 4.70 | 2.20 | 10.07 | 5.32 | 21.97 | 19.05 | 38.35 | 35.27 |
| 2700mm | 2400mm | 3.54 | 1.61 | 7.68 | 4.00 | 16.93 | 14.63 | 29.64 | 27.25 |
| 3000mm | 2700mm | 2.74 | 1.21 | 6.03 | 3.09 | 13.40 | 11.55 | 23.53 | 21.62 |
| 3300mm | 3000mm | n/a | n/a | 4.83 | 2.43 | 10.83 | 9.30 | 19.09 | 17.52 |
| 3600mm | 3300mm | n/a | n/a | 4.20 | 2.09 | 9.49 | 8.13 | 16.25 | 14.90 |
| Lintel Weight kg/m | | 34 | | 47 | | 72 | | 98 | |

| Fire-Spec Range | | Fire R2 | | | Fire R190 | | | Fire R13 | | |
|---|------------|---|---------|---------|--|---------|---------|---|---------|---------|
| Load Table Units suitable for 190mm wide walls Unfactored Loads in kN/m | |  | | |  | | |  | | |
| Maximum Stock Length Available | | 3600mm | | | 3600mm | | | 3600mm | | |
| | | Longer lengths available on request. | | | | | | | | |
| Available Range Finish | | Faced Colour | | | Faced Colour | | | Faced Colour | | |
| Fire Resistance Available (mins) | | 60 | 90 | 120 | 60 | 90 | 120 | 60 | 90 | 120 |
| Length | Clear Span | 190x145 | 190x145 | 190x145 | 190x215 | 190x215 | 190x215 | 190x290 | 190x290 | 190x290 |
| 900mm | 700mm | 81.86 | 80.56 | 62.31 | 126.49 | 126.49 | 127.02 | 162.20 | 162.20 | 162.77 |
| 1100mm | 900mm | 60.78 | 50.93 | 39.02 | 101.00 | 101.00 | 101.42 | 129.49 | 129.49 | 129.95 |
| 1200mm | 1000mm | 50.12 | 41.85 | 31.94 | 91.72 | 91.72 | 92.11 | 117.60 | 117.60 | 118.02 |
| 1500mm | 1200mm | 35.69 | 29.65 | 22.48 | 70.66 | 70.66 | 65.29 | 97.99 | 97.99 | 98.35 |
| 1800mm | 1500mm | 23.34 | 19.26 | 14.48 | 46.87 | 46.87 | 43.16 | 79.77 | 79.77 | 72.68 |
| 2100mm | 1800mm | 16.36 | 13.42 | 10.01 | 33.22 | 33.22 | 30.51 | 56.74 | 56.74 | 51.66 |
| 2400mm | 2100mm | 12.03 | 9.82 | 7.26 | 24.68 | 24.68 | 22.61 | 42.28 | 42.28 | 38.47 |
| 2700mm | 2400mm | 9.17 | 7.44 | 5.45 | 18.98 | 18.98 | 17.35 | 32.63 | 32.63 | 29.66 |
| 3000mm | 2700mm | 7.17 | 5.79 | 4.20 | 14.99 | 14.99 | 13.67 | 25.85 | 25.85 | 23.48 |
| 3300mm | 3000mm | 5.73 | 4.59 | 3.30 | 12.08 | 12.08 | 11.00 | 20.92 | 20.92 | 18.98 |
| 3600mm | 3300mm | 4.98 | 3.97 | 2.83 | 10.56 | 10.56 | 9.60 | 17.77 | 17.77 | 16.63 |
| Lintel Weight kg/m | | 66 | | | 98 | | | 132 | | |

| Fire-Spec Range | | Fire R7 | | | Fire S8 | | | Fire R14 | | |
|---|------------|---|---------|---------|--|---------|---------|---|---------|---------|
| Load Table Units suitable for 215mm wide walls Unfactored Loads in kN/m | |  | | |  | | |  | | |
| Maximum Stock Length Available | | 3600mm | | | 3600mm | | | 3600mm | | |
| | | Longer lengths available on request. | | | | | | | | |
| Available Range Finish | | Faced Colour | | | Faced Colour | | | Faced Colour | | |
| Fire Resistance Available (mins) | | 60 | 90 | 120 | 60 | 90 | 120 | 60 | 90 | 120 |
| Length | Clear Span | 215x145 | 215x145 | 215x145 | 215x215 | 215x215 | 215x215 | 215x290 | 215x290 | 215x290 |
| 900mm | 700mm | 90.15 | 85.07 | 62.99 | 138.94 | 138.94 | 139.44 | 178.60 | 178.60 | 179.07 |
| 1100mm | 900mm | 63.86 | 53.76 | 39.41 | 110.93 | 110.93 | 111.33 | 142.58 | 142.58 | 142.96 |
| 1200mm | 1000mm | 52.65 | 44.17 | 32.26 | 92.25 | 92.25 | 101.10 | 129.48 | 129.48 | 129.83 |
| 1500mm | 1200mm | 37.48 | 31.28 | 22.68 | 74.26 | 74.26 | 68.77 | 107.73 | 107.73 | 108.04 |
| 1800mm | 1500mm | 24.49 | 20.30 | 14.58 | 49.23 | 49.23 | 45.44 | 83.95 | 83.95 | 79.64 |
| 2100mm | 1800mm | 17.15 | 14.13 | 10.06 | 34.87 | 34.87 | 32.10 | 59.68 | 59.68 | 56.59 |
| 2400mm | 2100mm | 12.60 | 10.32 | 7.27 | 25.89 | 25.89 | 23.77 | 44.45 | 44.45 | 42.13 |
| 2700mm | 2400mm | 9.59 | 7.81 | 5.44 | 19.89 | 19.89 | 18.22 | 34.28 | 34.28 | 32.47 |
| 3000mm | 2700mm | 7.49 | 6.07 | 4.17 | 15.69 | 15.69 | 14.34 | 27.14 | 27.14 | 25.70 |
| 3300mm | 3000mm | 5.97 | 4.80 | 3.26 | 12.63 | 12.63 | 11.52 | 21.94 | 21.94 | 20.76 |
| 3600mm | 3300mm | 5.18 | 4.15 | 2.78 | 11.04 | 11.04 | 10.05 | 18.62 | 18.62 | 17.61 |
| Lintel Weight kg/m | | 75 | | | 111 | | | 150 | | |

Steel Range (L-Strip)



A range of Steel L-Shaped angle lintels suitable for brick and stone to carry the external leaf.

Available in galvanised (Pregalv G600) and stainless steel grade 304. Other specially designed steel lintels available upon request.

| L-Strip Range | | LG85 LS85 | LG85 Stone LS85 Stone | LG165 LS165 | LG165 Stone LS165 Stone | LG215 LS215 | LG215 Stone LS215 Stone |
|---|------------|--------------------------------------|----------------------------------|----------------------------------|----------------------------------|----------------------------------|----------------------------------|
| Load Table Units suitable for 90mm and 130mm wide walls Unfactored Loads in kN/m | | | | | | | |
| Maximum Stock Length Available | | 2100mm | 2100mm | 2700mm | 2700mm | 3600mm | 3600mm |
| | | Longer lengths available on request. | | | | | |
| Available Range Finish | | Galvanized Stainless Steel | Galvanized Stainless Steel | Galvanized Stainless Steel | Galvanized Stainless Steel | Galvanized Stainless Steel | Galvanized Stainless Steel |
| Length | Clear Span | 90x85 | 130x85 | 90x165 | 130x165 | 90x215 | 130x215 |
| 900mm | 700mm | 22.85 | 22.85 | 62.10 | 62.10 | 32.75 | 32.75 |
| 1100mm | 900mm | 14.63 | 14.63 | 39.75 | 39.75 | 20.96 | 20.96 |
| 1200mm | 1000mm | 12.09 | 12.09 | 32.85 | 32.85 | 17.32 | 17.32 |
| 1500mm | 1200mm | 8.02 | 8.02 | 21.15 | 21.15 | 11.50 | 11.50 |
| 1800mm | 1500mm | 5.37 | 5.37 | 13.25 | 13.25 | 7.69 | 7.69 |
| 2100mm | 1800mm | 3.42 | 3.42 | 8.51 | 8.51 | 5.51 | 5.51 |
| 2400mm | 2100mm | n/a | n/a | 5.46 | 5.46 | 4.14 | 4.14 |
| 2700mm | 2400mm | n/a | n/a | 3.54 | 3.54 | 3.22 | 3.22 |
| 3000mm | 2700mm | n/a | n/a | n/a | n/a | 2.58 | 2.58 |
| 3300mm | 3000mm | n/a | n/a | n/a | n/a | 2.11 | 2.11 |
| 3600mm | 3200mm | n/a | n/a | n/a | n/a | 1.86 | 1.86 |
| Lintel Weight kg/m | | 5 | | 7 | | 9 | |

Economy Range



A cost effective fully reversible unit for when you have a standard housing situation or small load situation.

All Economy lintels are suitable for use with L-Strip.

Finish

An ex-steel mould finish and made from wet cast concrete. May see small air holes on the surface, aggregate and concrete fines to bottom arrises. For use normally in plastered situations. For exposed situations see Fair Faced Range.








Order/Specification Code

Please see the Economy Load Tables (e.g. ER1, ER2 etc).

Identification

All Economy Range lintels are marked on one end with yellow paint.

The Economy Range is only manufactured in lengths up to 3m.

| Economy Range | | ER1 | ER2 | ER3 | ER4 | ER6 | ER7 | ER8 |
|-----------------------------|------------|---|---|---|---|---|---|---|
| Load Table | |  |  |  |  |  |  |  |
| Unfactored Loads in kN/m | | | | | | | | |
| Suitable for Foundation Use | | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Available Range Finish | | Standard | Standard | Standard | Standard | Standard | Standard | Standard |
| Length | Clear Span | 100x65 | 100x140 | 140x65 | 215x70 | 140x140 | 100x215 | 140x215 |
| 900mm | 700mm | 8.31 | 30.04 | 10.08 | 17.73 | 36.87 | 59.38 | 82.52 |
| 1100mm | 900mm | 5.07 | 18.80 | 6.13 | 10.81 | 23.06 | 47.40 | 56.61 |
| 1200mm | 1000mm | 4.10 | 15.39 | 4.96 | 8.76 | 18.87 | 40.95 | 46.66 |
| 1500mm | 1200mm | 2.83 | 10.83 | 3.42 | 6.04 | 13.25 | 28.83 | 32.81 |
| 1800mm | 1500mm | 1.78 | 6.97 | 2.13 | 3.79 | 8.51 | 18.90 | 21.46 |
| 2100mm | 1800mm | 1.19 | 4.81 | 1.42 | 2.55 | 5.86 | 13.27 | 15.03 |
| 2400mm | 2100mm | 0.84 | 3.49 | 0.99 | 1.79 | 4.23 | 9.78 | 11.04 |
| 2700mm | 2400mm | n/a | 2.61 | 0.71 | 1.30 | 3.15 | 7.46 | 8.39 |
| 3000mm | 2700mm | n/a | 2.01 | 0.52 | 0.96 | 2.41 | 5.85 | 6.55 |
| Lintel Weight kg/m | | 16 | 34 | 22 | 34 | 47 | 51.6 | 72 |

| Economy Range | | ER1 On Edge 65x100 | ER2 On Edge 140x100 | ER3 On Edge 65x140 | ER4 On Edge 70x215 | ER6 On Edge 140x140 | ER7 On Edge 215x100 | ER8 On Edge 215x140 |
|--------------------|------------|--------------------------|---------------------------|--------------------------|--------------------------|---------------------------|---------------------------|---------------------------|
| Length | Clear Span | | | | | | | |
| 900mm | 700mm | 12.27 | 22.53 | 19.85 | 40.89 | 36.87 | 40.97 | 62.25 |
| 1100mm | 900mm | 7.59 | 13.91 | 12.43 | 31.73 | 23.06 | 25.34 | 38.96 |
| 1200mm | 1000mm | 6.18 | 11.33 | 10.18 | 26.16 | 18.87 | 20.65 | 31.88 |
| 1500mm | 1200mm | 4.31 | 7.89 | 7.16 | 18.42 | 13.25 | 14.42 | 22.42 |
| 1800mm | 1500mm | 2.75 | 5.02 | 4.61 | 12.07 | 8.51 | 9.19 | 14.42 |
| 2100mm | 1800mm | 1.89 | 3.42 | 3.18 | 8.47 | 5.86 | 6.30 | 9.95 |
| 2400mm | 2100mm | 1.35 | 2.45 | 2.31 | 6.24 | 4.23 | 4.53 | 7.20 |
| 2700mm | 2400mm | n/a | 1.80 | 1.73 | 4.76 | 3.15 | 3.37 | 5.39 |
| 3000mm | 2700mm | n/a | 1.36 | 1.33 | 3.73 | 2.41 | 2.57 | 4.14 |
| Lintel Weight kg/m | | 17 | 34 | 22 | 34 | 47 | 51.6 | 72 |

Padstone Range

| Padstones | |
|-----------------|--|
| Section mm | |
| 100 x 140 x 100 | |
| 215 x 140 x 100 | |
| 330 x 140 x 100 | |
| 440 x 140 x 100 | |
| | |
| 140 x 140 x 140 | |
| | |
| 215 x 100 x 215 | |
| 215 x 140 x 215 | |
| 215 x 190 x 215 | |
| 215 x 215 x 215 | |
| | |
| 300 x 100 x 215 | |
| 300 x 140 x 215 | |
| 300 x 190 x 215 | |
| 300 x 215 x 215 | |
| 330 x 100 x 215 | |
| 330 x 140 x 215 | |
| 330 x 190 x 215 | |
| 330 x 215 x 215 | |
| | |
| 330 x 100 x 290 | |
| 330 x 140 x 290 | |
| 330 x 190 x 290 | |
| 330 x 215 x 290 | |
| | |
| 440 x 100 x 215 | |
| 440 x 140 x 215 | |
| 440 x 190 x 215 | |
| 440 x 215 x 215 | |
| | |
| 440 x 100 x 290 | |
| 440 x 140 x 290 | |
| 440 x 190 x 290 | |
| 440 x 215 x 290 | |

| L-Shaped Padstone - Section mm | |
|--------------------------------|--|
| 215/215 x 100 x 215 | |
| 300/300 x 100 x 215 | |
| 330/330 x 100 x 215 | |
| 440/440 x 100 x 215 | |
| 330/330 x 140 x 215 | |
| 440/440 x 140 x 215 | |



A full range of padstones are available with a strength that is a minimum of 50N/mm² and are suitable to take special fixing or any other site situations. We have a large range of 29 sections available as standard stock items with an additional 6 L-shaped padstones. Specials can be made also at a competitive price and the quality assures you that the concrete will take any loads placed upon it. Special strength higher than 50N/mm² are also available on request.

COSHH Information

1. Identification

Identification of the Lintel/Preparation and the Company

Product Name(s)

1. Naylor Economy
2. Naylor Hi-Spec
3. Naylor Fair Faced
4. Naylor Fire-Spec
5. Naylor Chem-Spec
6. Naylor Padstones
7. Naylor Ultra-Fire
8. Naylor Faced Fire
9. Naylor Colour-Spec

Company

Naylor Lintels Limited
Milner Way, Longlands Industrial Estate
Ossett, West Yorkshire, WF5 9JE

Telephone

+44 (0) 1924 267286

Fax

+44 (0) 1924 265674

Intended Use

- 1.2.3.5. The support of Brick and Block work openings
- 4.7. The support of Brick and Block work openings in Fire performance walls.
6. The spreading of loads in Brick and Block work walls.

2. Composition

Information on Ingredients

Hazardous Ingredients

Ground Limestone Whitening
Portland Cement
Mica

3. Hazards Identification

Main Hazards

Irritating to skin, Risk of serious damage to eyes during cutting, May cause sensation by skin contact, Straining during lifting, finger entrapment during lifting. Cuts to hands and fingers from corners of units.

4. First Aid Measures

Skin Contact

Irritation to Skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing, seek medical attention if irritation or symptoms persist.

Eye contact

Irritation to eyes. Rinse immediately with plenty of

sterile eyewash holding the eyelids open. Seek medical attention if irritation or symptoms persist.

Inhalation

Irritating to respiratory system. Move the exposed person to fresh air. Seek medical attention.

Ingestion

Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

Lacerations

Clean all cuts with an antiseptic wipe thoroughly and cover with a sterile dressing. Monitor. Seek medical attention.

Back injury

Stabilise casualty and seek medical attention immediately, DO NOT MOVE THE INJURED PERSON UNLESS SITUATION WOULD FURTHER AFFECT THE LIFE OF THE INJURED PERSON.

5. Fire Fighting Measures

Extinguishing

Use extinguishing Media appropriate to surrounding fire conditions.

6. Accidental Release Measures

Personal

Ensure adequate ventilation of the working area. Wear suitable protective equipment for the task.

- Dust masks to comply with EN 149 FFFP1 or EN1449 FFFP2S during cutting or surface hardening of concrete.
- Eye protection during cutting to comply with appropriate British standards.
- Ear protection during cutting to comply with appropriate British standards.
- Clothing particular to hands and feet, suitably reinforced footwear and chemical resistant gloves (PVC). Long sleeved garments and long trousers to protect from abrasion.

Environmental

All waste from cutting should be swept up and also disposed of. Do not allow waste product to enter drains, unused hardened concrete although inert should be disposed of in accordance with local legal requirements.

Clean up methods

Sweep up. Transfer to suitable labelled containers for disposal. Clean cutting area with plenty of water.

7. Handling

Handling, Transportation and Storage

Handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best manual handling considerations when handling, carrying and dispensing.

Lifting

When using mechanical plant only one layer of units should be lifted at any one time and should be supported at both ends. Units should be handled carefully to avoid heavy blows, dropping or reverse bending. Considerations should be given to prevailing weather conditions particularly wind and rain and no lifting should be directly above work areas. Due to the weight of the units a check of the lifting capabilities of the machinery involved should be made to ensure this is not exceeded prior to any lift taking place.

Storage

Keep in a cool, dry well ventilated area. Stacking should be on a firm level area. With the bearers directly over one another supporting both ends of the units. Examine all units for cracks and damage and if present do not use without referral to Naylor Lintels.

Transportation

Care should be taken in stacking of the pre cast units relative to their size and weight and should be off loaded on to a firm and level site. Loads should be secured to comply with the operators licence for the transportation of non-hazardous products. The product is not classified as dangerous for carriage.

8. Fixing of Units

Safety

The work area should be prohibited to all other personnel and the units lifted in accordance with manual handling procedures or lifting requirements onto structural sound level bearings. If bricks are used as the support all voids should be filled and cured before the placing of the units.

Requirements

Lintels should be placed in accordance with the structural drawings and should have adequate length to ensure that adequate end bearing for the length of the unit is available. Bearing should be structurally capable of dealing with load exerted by the unit, and any imposed block, floor and roof load. Blocks should be accurate and square and any cutting should be done using a block/disc cutter. Once units are placed there should be minimal joints between all components. Any fixing into the units should avoid any damage to the steel tendons located inside of the units and the use of shot fixings should be avoided.

9. Toxicological Information

Ground Limetstone, Whiting

Oral Rat LD50 = 5001 mg/kg.

Acute Toxicity

Inhalation of dust may cause shortness of breath.

Sensitization

May cause sensitization by skin contact.

Repeated or prolonged exposure

May cause dermatitis.

Further Information

Information on other Naylor Group Products may be obtained by **faxing this form** back to Liz Hudston on 01226 794415

Clayware

Please ✓ tick

- Drainage Design Handbook**
- Denlok** - Microtunnelling Pipes
- Densleeve and Denseal** - Building and Sewers/
Surface Water Drainage
- Hathernware Pipes** - For Aggressive Environments
- Tiles** - For Sewage Treatment

Plastics

- Access Box Brochure**
- Land Drain**

Other Products

- Band-Seal** - Flexible Couplings
- Aqua-Lite** - Linear Drainage
- Garden Pots**

Name: _____

Company: _____

Address: _____

_____ Post Code: _____

Tel: _____ Fax: _____

E-mail: _____



Naylor Industries plc - more than 100 years of production and supply to the Construction Industry

- Vitrified clay pipe systems for trench and trenchless installation
- Hathernware - Chemical Drainage and Industrial Ceramics
- Band-Seal couplings for the repair of and connections into existing pipelines
- Plastic Land Drainage, Twinwall Ducting Systems and Access Boxes
- Yorkshire Flowerpots, a range of frostproof plant pots



**NAYLOR CONCRETE
PRODUCTS LIMITED**

NAYLOR LINFELS DIVISION
MILNER WAY, LONGLANDS
INDUSTRIAL ESTATE
OSSETT, WEST YORKSHIRE
WF5 9JE

TELEPHONE: 01924 267286
FACSIMILE: 01924 265674
EMAIL: LINFELS@NAYLOR.CO.UK
WEB: WWW.NAYLORLINFELS.CO.UK